

Specifications

MODEL		AB-IVProtector	
Descripción		Time delay it surge protection	
Input	Voltage / Frequency	110/115/120/127 VAC / 50/60 Hz	
	Rango de voltaje	90 ~ 140 VAC	
	Capacity	15 Amps /1800 Vatios	
	Outlets	Nema 5-15P it rotation 0 ~350 degrees	
	itc	Turn on and turn off button	
Output	Voltage	the same as input	
	Voltage range	90 ~ 140 VAC	
	Capacity	15 Amp /1800	
	Outlets	1 x Nema 5-15P	
Features	15 sec. / 30 sec. / 3 min.		
	Low voltage disconnect	90 VAC	
	5SFDU	140 VAC	
Supresor	5SFDU	900 Joules	
LED Indicators	<ul style="list-style-type: none"> Lo input voltage led /15 sec Normal led / 30 sec Hig input voltage led / 3 min. AC input voltage is too lo LED LED 	Led is ON	
		Led is OFF	
		standby mode	Voltage protection starts it 15 sec delay
			Voltage protection starts it 30 sec delay
			Voltage protection starts it 3 min. sec delay
		mode	Surge protector is in off mode
			input disconnected
	the led is flash in		

*Las especificaciones están sujetas a cambios sin previo aviso.